



Porty L 1200

Article number: 4962

- Definitely faster, smaller, lighter, but with stronger output performance than units with lead-gel cell battery
- Only 5,9 kg total weight but 1200 Ws output
- Extremely fast flash recycle times from 0,2 s
- Extremely short flash duration up to 1/5.160 s (with Speed Head)
- Choice of symmetric or asymmetric power distribution via the „A“ or „B“ socket
Individual settings in 1/10 f-stop increments
- Integrated Profoto Air radio, Hensel Strobe Wizard Plus and freemask receiver, switchable
Radio remote functions: output adjustment, triggering, modelling light, standby. Full remote control with both systems, manufacturer compatible.
- Integrated radio antenna for optimum protection
- Metal housing with sturdy, protective rubber profile
- Special ergonomical handle bar for carrying, with integrated spare fuses
- Optional use of AC mains switch drawer instead of power pack
- Output adjustment in 1/10 f-stop increments
- Output range of 7 f-stops
- Large 7-segment performance indicator
- Connector socket for round plugs / Hensel Porty connector and Pro Mini / 20-pol. long plug via adapter
- USB port for software updates
- Durable foil surface with ‚real‘ push-buttons for ‚feel good‘ use
- New foil surface with clearly detectable imprint around the push-buttons. Optimal for your sense of touch
- Hensel usage concept – name and position of switches and control units are generally the same.
Working without rethinking!

- APD, internal power reduction when reducing power output
- Built-in photocell, separately switchable
- Synchronous socket for standard cord 6,3 mm
- Test button for manual test firing
- Very low synchronous voltage protects digital cameras
- Thermal monitoring of performance electronics

Technical data

Rated energy:	1200 J
Aperture at 100 ASA, t 1/60, 12" reflector, power 10.0	
1 m distance:	f 128 0/10
2 m distance:	f 64 0/10
Flash duration, t 0,5, power 8.0	
1 EH Pro Mini 1200P Speed:	1/5160 s
1 EH Pro Mini 1200P:	1/2380 s
Abbrezeit, t 0,1, power 8.0	
1 EH Pro Mini 1200P Speed:	1/2030 s
1 EH Pro Mini 1200P:	1/970 s
Abbrezeit, t 0,5, power 10.0	
1 EH Pro Mini 1200P Speed:	1/1590 s
1 EH Pro Mini 1200P:	1/940 s
Abbrezeit, t 0,1, power 10.0	
1 EH Pro Mini 1200P Speed:	1/520 s
1 EH Pro Mini 1200P:	1/290 s
Number of flashes per battery pack charge, 100% power*:	max. 210
Charging time to 100% power:	2,1 s
Charging time to min. power:	0,2 s
Output adjustment flash energy:	10 - 4 = 7 f-stop
Output distribution:	symmetrical or asymmetrical
Flash sockets:	2 (round sockets)
Modeling light, operation with battery pack:	Halogen lamp 2 x 60 W
Modeling light, operation with AC mains adapter drawer:	Halogen lamp 2 x 650 W
Specification of battery pack:	Lithium ion, rechargeable U (rated) = 14,6 V / 6,5 Ah, weight 1,2 kg
Charging time battery pack:	2 h / 100% 45 min. / 80%
Compatible flash heads:	Hensel EH Pro Mini (Speed), EH Pro Mini P (Speed)
Fuse for modeling lamp/charge:	2 x M 10 AH
Weight with battery pack:	5,9 kg
Dimensions (L x W x H):	22,5 x 20 x 21,5 cm

* Modeling lamp OFF

Technical data are subject to change. The listed values are guide values and should not be understood as binding in a legal sense. The values can differ due to tolerances in used components. Values attained at 230 V / 50 Hz voltage. Date of revision: August 2011